## **PROCEEDINGS OF SPIE**

# Laser Resonators, Microresonators, and Beam Control XXII

Alexis V. Kudryashov Alan H. Paxton Vladimir S. IIchenko Andrea M. Armani Editors

3–6 February 2020 San Francisco, California, United States

Sponsored and Published by SPIE

Volume 11266

Proceedings of SPIE 0277-786X, V. 11266

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

The papers in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. Additional papers and presentation recordings may be available online in the SPIE Digital Library at SPIEDigitalLibrary.org.

The papers reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from these proceedings:

Author(s), 'Title of Paper," in Laser Resonators, Microresonators, and Beam Control XXII, edited by Alexis V. Kudryashov, Alan H. Paxton, Vladimir S. Ilchenko, Andrea M. Armani, Proceedings of SPIE Vol. 11266 (SPIE, Bellingham, WA, 2020) Seven-digit Article CID Number.

ISSN: 0277-786X ISSN: 1996-756X (electronic)

ISBN: 9781510632950 ISBN: 9781510632967 (electronic)

Published by **SPIE** P.O. Box 10, Bellingham, Washington 98227-0010 USA Telephone +1 360 676 3290 (Pacific Time) · Fax +1 360 647 1445 SPIE.org Copyright © 2020, Society of Photo-Optical Instrumentation Engineers.

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of copying fees. The Transactional Reporting Service base fee for this volume is \$21.00 per article (or portion thereof), which should be paid directly to the Copyright Clearance Center (CCC), 222 Rosewood Drive, Danvers, MA 01923. Payment may also be made electronically through CCC Online at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher. The CCC fee code is 0277-786X/20/\$21.00.

Printed in the United States of America by Curran Associates, Inc., under license from SPIE.

Publication of record for individual papers is online in the SPIE Digital Library.



**Paper Numbering:** Proceedings of SPIE follow an e-First publication model. A unique citation identifier (CID) number is assigned to each article at the time of publication. Utilization of CIDs allows articles to be fully citable as soon as they are published online, and connects the same identifier to all online and print versions of the publication. SPIE uses a seven-digit CID article numbering system structured as follows:

• The first five digits correspond to the SPIE volume number.

• The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc. The CID Number appears on each page of the manuscript.

### Contents

ix Conference Committee

#### **CRYSTALLINE WGM MICRORESONATORS AND APPLICATIONS I**

- 11266 06
   Electro-optic based adiabatic frequency conversion in a non-centrosymmetric microresonator

   [11266-4]
   [11266-4]
- 11266 07High-precision measurement of a propagation loss of low-loss single-mode optical<br/>waveguides on lithium niobate on insulator [11266-5]
- 11266 09
   Juggling with light: powerful second-order nonlinear optical effects in whispering gallery resonators (Invited Paper) [11266-7]
- 11266 0A Ultra-low loss lithium niobate photonics (Invited Paper) [11266-8]

### KERR OPTICAL FREQUENCY MICROCOMBS WITH WGM

- 11266 OF Silicon oxynitride microresonators for Kerr frequency combs [11266-13]
- 11266 0G Frequency comb generation in non-centrosymmetric optical microresonators [11266-14]
- 11266 01 Ultra-high-Q whispering-gallery mode resonators in the pulsed-pump regime [11266-16]

### CONFIGURABLE WGM AND EXCITATION

- All-optically triggerable organic/inorganic photonic devices (Invited Paper) [11266-17]
- 11266 0M Optically tunable on-chip microresonator [11266-20]
- 11266 0N Exciting Whispering Gallery Modes in liquid microdrops using sub-micron size tapered fibers [11266-21]

### LASERS WITH WGM RESONATORS

11266 00 780 nm narrow-linewidth self-injection-locked WGM lasers (Invited Paper) [11266-23]

## 11266 OP On-chip Brillouin lasers based on 10 million-Q chalcogenide resonators without direct etch process [11266-24]

11266 0Q Tunable single-frequency lasing in whispering gallery resonators [11266-25]

### BEAM SHAPING I

11266 0Z Generation of Bessel type beams via phase shifted axicons encoded in geometrical phase elements [11266-35]

### **BEAM SHAPING II**

1126612 Dynamic coherent beam combining based on a setup of microlens arrays [11266-38]

### LASER MODE CONTROL

- 1126613 Multiline oscillation of Q-switched cavity-dumped CO<sub>2</sub> laser with intracavity diffraction grating [11266-39]
- 1126614 Three-level Nd:YLF Raman laser directly pumped by a beam shaped diode bar [11266-40]
- 1126615 Design of an external cavity semiconductor laser for intra-cavity beam combining [11266-41]
- 1126616 Thermal and population induced lensing in Alexandrite lasers [11266-42]
- 1126617 Dynamically stable lasers from commercial Nd: YAG modules with high beam quality and single-frequency: The correct choice of the fundamental waist size at the rod [11266-43]
- 1126618 Multi-kilowatt fibre laser with azimuthal mode output beam for advanced material processing [11266-44]

### ADAPTIVE OPTICS, LASER DIAGNOSTICS, NONLINEAR PROPAGATION

- 11266 19 Applicability of small size wavefront correctors to compensate for wavefront distortions in laser systems [11266-45]
- 112661A M-squared laser measurement as simple as measuring laser power [11266-46]
- 112661B Focusing laser beam through pinhole using stacked-actuator deformable mirror [11266-47]

### POSTER SESSION

11266 1D	Extra-cavity laser beam shaping using an Nd: YAG amplifier [11266-49]
11266 1E	Versatile bio-organism detection using microspheres for future biodegradation and bioremediation studies [11266-50]
11266 1F	Microresonators for compact optical sensors (µRCOS) for gas detection [11266-51]
11266 1G	A stretched-pulse mode-locked laser source at a central wavelength of 1275 nm [11266-52]
11266 1H	Micro-bottle resonator as sensors using whispering gallery modes [11266-53]
11266 1J	Design of efficient Gauss to top-hat converters using geometrical phase elements inscribed in the glass by femtosecond laser pulses [11266-55]
11266 1L	Miniature bimorph deformable mirror for laser beam shaping [11266-57]
11266 1M	Iron: zinc selenide laser, pumping with pulse width that is shorter than or comparable to the population-inversion lifetime [11266-58]