

2019 IEEE 26th International Symposium on Physical and Failure Analysis of Integrated Circuits (IPFA 2019)

Hangzhou, China
2 – 5 July 2019



IEEE Catalog Number: CFP19777-POD
ISBN: 978-1-7281-3553-3

**Copyright © 2019 by the Institute of Electrical and Electronics Engineers, Inc.
All Rights Reserved**

Copyright and Reprint Permissions: Abstracting is permitted with credit to the source. Libraries are permitted to photocopy beyond the limit of U.S. copyright law for private use of patrons those articles in this volume that carry a code at the bottom of the first page, provided the per-copy fee indicated in the code is paid through Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923.

For other copying, reprint or republication permission, write to IEEE Copyrights Manager, IEEE Service Center, 445 Hoes Lane, Piscataway, NJ 08854. All rights reserved.

****** This is a print representation of what appears in the IEEE Digital Library. Some format issues inherent in the e-media version may also appear in this print version.***

| | |
|-------------------------|-------------------|
| IEEE Catalog Number: | CFP19777-POD |
| ISBN (Print-On-Demand): | 978-1-7281-3553-3 |
| ISBN (Online): | 978-1-7281-3552-6 |
| ISSN: | 1946-1542 |

Additional Copies of This Publication Are Available From:

Curran Associates, Inc
57 Morehouse Lane
Red Hook, NY 12571 USA
Phone: (845) 758-0400
Fax: (845) 758-2633
E-mail: curran@proceedings.com
Web: www.proceedings.com

CURRAN ASSOCIATES INC.
proceedings
.com

TABLE OF CONTENTS

| | |
|---|-----------|
| INTEGRATING NI LABVIEW IN SOFT DEFECT LOCALIZATION OF TEMPERATURE DEPENDENT VOLTAGE FAILURE | 1 |
| <i>P. Llameria, C. Garcia-Awitan</i> | |
| A STUDY ON AN ABNORMAL OXIDATION ISSUE OF COPPER BONDING WIRE | 7 |
| <i>L. Jinzhi, S. Jianbo, Z. Lei, C. Yan, C. Nan, Y. Qinghong, F. Chao, H. Younan, L. Xiaomin</i> | |
| EFFECT OF PRIMARY KNOCKED-ON ATOMS ON CONDUCTIVITY COMPENSATION IN N-TYPE 4H-SIC IRRADIATED BY 1 MEV ELECTRONS, 25 MEV C IONS AND 40 MEV SI IONS | 11 |
| <i>G. Ma, Y. Zhang, H. Li, C. Liu, C. Qi, Y. Wei, T. Wang, S. Dong, M. Huo</i> | |
| SILICON PRECIPITATES COUNTS AND SIZE STUDY IN ALUMINIUM BOND PADS | 16 |
| <i>L. Lee, M. MohdNoor, M. Raj</i> | |
| A SINGLE-EVENT IRRADIATION FAILURE ANALYSIS TEST SYSTEM FOR HIGH SPEED DIGITAL-TO-ANALOG CONVERTER..... | 20 |
| <i>Y. Wei, J. Li, Z. Yu, C. Chen, J. Liu, X. Wen, J. Wang</i> | |
| ENHANCED PACKAGE FAULT ISOLATION METHOD USING TIME DOMAIN REFLECTOMETRY (TDR) INCORPORATION WITH MATHEMATICS | 25 |
| <i>L. Lee, K. Chua</i> | |
| CYCLE-SHIFT SCAN CHAIN FAILURE ANALYSIS USING SINGLE PULSE TEST PATTERN | 28 |
| <i>P. Eric, C.-L. Choong, Y. Chai</i> | |
| NANOPROBING ANALYSIS ON MOSFET CURRENT DRIFT CAUSED BY GATE OXIDE DEFECT..... | 32 |
| <i>W. Huang, T. Chua, H. Zhang, C. Song</i> | |
| USING HIGHER ACCELERATING VOLTAGE OF SEM TO DIG OUT IMPLANT DEFECTS..... | 37 |
| <i>W. Hsu, Y. Shu, C. Pan</i> | |
| DEGRADATION BEHAVIOUR OF ELECTRICAL PROPERTIES OF INVERTED METAMORPHIC FOUR-JUNCTION (IMM4J) SOLAR CELLS UNDER 1 MEV ELECTRON IRRADIATION | 41 |
| <i>Z. Yanqing, M. Guoliang, W. Tianqi, L. Chaoming, H. Mingxue, Q. Chunhua</i> | |
| THE PROBE MARKER DISCOLORATION ON AL PAD AND WAFER STORAGE | 44 |
| <i>W. Hsieh, H. Lin, V. Chen, I. Ou, Y. Lou</i> | |
| TEM-EDX LINE SCAN TO INVESTIGATE O₂ DIFFUSION ACROSS PHYSICAL VAPOR DEPOSITED AL-CU LAYER..... | 48 |
| <i>W. Wai, O. Sheng, L. Jia, L. Yien</i> | |
| COMBINED APPLICATION OF AFM-XRD-SIMS TO CHARACTERIZE CRYSTAL PROPERTIES IN ELECTROLESS NICKEL METAL INDUCED BY TRACE CONTAMINANTS..... | 52 |
| <i>W. Wai, L. Cheat, L. Sing, Z. Nurhanani</i> | |
| ANALYSIS OF SEE MODES IN FERROELECTRIC RANDOM ACCESS MEMORY USING HEAVY IONS..... | 56 |
| <i>J.-N. Wei, H.-X. Guo, F.-Q. Zhang, G. Guo, C.-H. He</i> | |
| HIGH RESOLUTION MAPPING OF DEFECTS AT SIO₂/SIC INTERFACES BY LOCAL-DLTS BASED ON TIME-RESOLVED SCANNING NONLINEAR DIELECTRIC MICROSCOPY | 61 |
| <i>Y. Yamagishi, Y. Cho</i> | |
| RADIATION-HARDENED MEMORY CELL FOR ULTRALOW POWER SPACE APPLICATIONS | 65 |
| <i>C. Qi, G. Ma, T. Wang, C. Liu, L. Xiao, H. Li, Y. Zhang, K. Guo, M. Huo, G. Zhai</i> | |
| THE LIKELIHOOD OF MULTIPLE BIT-FLIPS DUE TO NEUTRON STRIKES AND ITS IMPLICATIONS ON CIRCUIT DESIGNS..... | 70 |
| <i>N. Rao, M. Desai</i> | |
| ROBUST PACKAGE DEVELOPMENT FOR AUTOMOTIVE APPLICATION | 78 |
| <i>C. Chung, C. Fang, C. Keng, X. Zhang</i> | |
| IRRADIATION EFFECTS OF 1 MEV ELECTRON ON MONOLAYER MOS₂ FIELD EFFECT TRANSISTORS | 81 |
| <i>Y. Zhang, G. Ma, X. Zheng, Z. Hua, J. Zhou, H. Li, C. Liu, Y. Wei, T. Wang, C. Qi, S. Dong, M. Huo</i> | |
| ADVANCED TEM APPLICATION IN 10NM BELOW TECHNOLOGY NODE DEVICE ANALYSIS | 85 |
| <i>H. Yang, Y. Li, H. Zhu, X. Yin, A. Du</i> | |

| | |
|---|-----|
| SIMULTANEOUS 2D CARRIER POLARITY (DC/DV) AND DENSITY (DC/DZ) DISTRIBUTION MEASUREMENT OF SI/SIC MOSFET BASED ON SCANNING NONLINEAR DIELECTRIC MICROSCOPY | 89 |
| <i>T. Yamaoka, T. Aiso, K. Watanabe, Y. Shikakura, T. Ueno, K. Tamura, K. Mizuguchi</i> | |
| BACKSIDE PREPARATION BY MILLING APPROACH OF MODULE DEVICE FOR FAILURE ANALYSIS..... | 94 |
| <i>K. Fulla Jr., M. Acedillo, F. Cruz, F. Valiente</i> | |
| DESIGN AND VERIFICATION OF SRAM SELF-DETECTION REPAIR BASED ON ECC AND BISR CIRCUIT..... | 100 |
| <i>Y. Zhang, Y. Piao, M. Huo, T. Wang, G. Ma, C. Liu, J. Ma, K. Guo, C. Qi</i> | |
| NEW APPROACHES IN ESD RISK MEASUREMENT OF PCB ASSEMBLING MACHINES AND ESD COUNTERMEASURES | 105 |
| <i>P. Jacob</i> | |
| DESIGN OF RADIATION-HARDENED IMAGE COMPRESSOR BASED ON LOSSLESS JPEG-LS | 111 |
| <i>C. Qi, J. Ma, M. Huo, T. Wang, G. Ma, C. Liu, Y. Piao, K. Guo, Y. Zhang</i> | |
| THE SOLUTIONS OF BIT LINE FAILURE ANALYSIS: LOW KV E-BEAM, EBAC AND LVI..... | 116 |
| <i>L. Chang, R. Wang, A. Chang, S. Wang, Y. Chang, C. Song</i> | |
| A NOVEL MIM SANDWICH STRUCTURE OF THE SCM PROBE FOR TOOL INSPECTION | 120 |
| <i>Y. Huang, Y. Li, C. Tsai, C. Pan</i> | |
| ADVANCED 3D OPTICAL IMAGING FOR DIE SURFACE TOPOGRAPHIC ANALYSIS | 124 |
| <i>L.-S. Yeoh, H.-L. Ong, K.-C. Chong, S. Li</i> | |
| COMPARISON OF CL EFFECT ON AU-AL AND CU-AL HTS AND BHAST WIRE BOND RELIABILITY PERFORMANCE | 129 |
| <i>W. Bisheng, L. Jinzhi, Z. Xi, L. Xiaomin, H. Younan, T. Weikok, Y. Boonhwa, M. Songlin, Y. Qinghong</i> | |
| SELF-HEATING AWARE EM RELIABILITY PREDICTION OF ADVANCED CMOS TECHNOLOGY BY KINETIC MONTE CARLO METHOD | 135 |
| <i>L. Cai, Y. Zhao, W. Chen, P. Huang, X. Liu, X. Zhang</i> | |
| SYSTEMATIC STUDY ON FAILURE INFORMATION OF THICK FILM HYBRID INTEGRATED CIRCUIT | 140 |
| <i>Z. Xiaowen, L. Hongjie, L. Xing</i> | |
| THE CASE OF FAILURE ANALYSIS OF THE PCBA WIRE CORROSION UNDER HIGH RELIABILITY REQUIREMENTS | 145 |
| <i>J. Zheng, Y. Yang, J. Shen, L. Ma, S. He</i> | |
| VERTICAL SILICON-CONTROLLED RECTIFIER FOR ESD PROTECTION UNDER 28NM PS PROCESS..... | 149 |
| <i>Z.-K. Xu, H.-Y. Shen, T. Hu, W. Guo, S.-R. Dong</i> | |
| IMPROVED LDMOS FOR ESD PROTECTION OF HIGH VOLTAGE BCD PROCESS | 152 |
| <i>H.-Y. Shen, S.-R. Dong, Z.-K. Xu, T. Hu, G. Wei, H. Wei</i> | |
| SI NANO-CRYSTAL SIZE AND STRUCTURAL DEFECT CHARACTERIZATION USING ELECTRON MICROSCOPES | 156 |
| <i>E. Sebastian, J. Zhu, Z. Mo</i> | |
| BACKSIDE AND TOPSIDE OBIRCH DEFECT LOCALIZATION ON MULTI-LAYER FINGER STRUCTURE MOSFET CAPACITOR WITH THE AID OF FOCUSED ION BEAM (FIB) | 160 |
| <i>R. Apolinaria, F. Cruz, F. Valiente</i> | |
| PBTI STUDY IN NATIVE HIGH VOLTAGE DEVICE..... | 165 |
| <i>B. Tsai, Z. Peng, H. Chuang, C. Chen, C. Hsu</i> | |
| OPTICAL FAILURE ANALYSIS ON PULSED SIGNALS EMBEDDED IN LOGIC CLOUD - A CASE STUDY OF LASER VOLTAGE TRACING | 168 |
| <i>Y. Sun, D. Lu, D. Mark, C. Di, J. Fan, N. Leslie</i> | |
| CASE STUDY ON PACKAGE LEVEL DEFECT LOCALIZATION THROUGH OPTIMIZED LOCK-IN THERMOGRAPHY FREQUENCY | 172 |
| <i>C. Casabuena, E. De La Cruz</i> | |
| PERFORMANCE VARIABILITY AND ANALOG BEHAVIOR OF MEMRISTIVE DEVICES WITH NEW TRANSITION METAL CARBIDE | 176 |
| <i>F. Gao, Y. Chen, Y. Li, M. Zhang, Y. Wang, N. He, X. Shen, E. Hu, X. Wan, X. Gong, Y. Guo, X. Lian, Y. Tong</i> | |
| INCREASED FAULT ISOLATION EFFICIENCY BY USING SCAN CELL VISUALIZER FOR SCAN CHAIN FAILURES | 182 |
| <i>P. Wei, F. Sheng, N. Choo, K. Serrels, K. Ku, C. Lin, C.-Y. Tang</i> | |
| A FAILURE ANALYSIS OF A SOP IC CREEP CORROSION ON POWER MODULE..... | 191 |
| <i>W. Zhang, Y. Lee, Y. Zhang</i> | |

| | |
|--|-----|
| ANALYSIS OF A NOVEL EOS FAILURE DUE TO STRAY VOLTAGE DURING ICT TESTING | 195 |
| <i>W. Zhang, Y. Zhang, Y. Lee</i> | |
| CASE STUDY OF ON-BOARD OPTICAL MODULE FAILURE INDUCED BY PDMS | 198 |
| <i>Y. Yu, Y. Lee</i> | |
| AN IMPROVED ANALYSIS METHOD ON SI-PHOTONICS WAVEGUIDE SIDEWALL ROUGHNESS | 201 |
| <i>H. Tan, X. Zhu, P. Ang, Y. Zhao, K. Menon, Y. Pan, C. Chen, P. Tan</i> | |
| ROOT CAUSE ANALYSIS ON ANALOG CIRCUIT USING TR-LADA | 205 |
| <i>L. Winson, P. Angeline, G. Ranganathan, A. Girish, R. Krishnan</i> | |
| A NEW STUDY OF BACKEND PROCESS ON 0.18UM BCD NLDMOS ON-STATE BV CHARACTERISTICS | 210 |
| <i>S. Chen, F. Lin, B. Yang, C. Li, Y. Huang</i> | |
| A STUDY OF N-LDMOS OFF-STATE BREAKDOWN DEGRADATION WITH 0.18μM BCD TECHNOLOGY | 214 |
| <i>F. Lin, B. Yang, G. Sun, S. Chen, C. Li, Y. Huang, Q. Wang, S. Liu</i> | |
| ADVANCED METHOD TO LOCATE THE DEFECT ON ZENER DIODE TO AVOID CUTTING THE CIRCUIT IN FAILURE ANALYSIS | 218 |
| <i>X. Qian, L. Tian, G. Wen, H. Zhang, X. Li</i> | |
| DEFECT DENSITY REDUCTION OF THIN SIO2 MOSFET THROUGH OXIDATION PRE-CLEANING IMPROVEMENT - A FAST WAFER LEVEL RELIABILITY MONITORING | 222 |
| <i>M. Kamaruddin, N. Soin, C. Veriven, C. How, C. Ang</i> | |
| HOW TO DETERMINE FLUORINE CONTAMINATION LEVEL ON A NORMAL AL BONDPAD? | 226 |
| <i>H. Younan</i> | |
| USING MICROPROBE TO ENHANCE DIE LEVEL STATIC FAULT ISOLATION IN COMPLEX IC | 230 |
| <i>D. Nagalingam, A. Quah, S. Moon, S. Parab, P. Ng, S. Ting, H. Ma, C. Chen</i> | |
| ELECTRICAL PERFORMANCES AND PHYSICS BASED ANALYSIS OF 650V E-MODE GAN DEVICES AT HIGH TEMPERATURES | 235 |
| <i>C. Zhang, S. Li, S. Liu, J. Wei, W. Wu, W. Sun</i> | |
| ELECTRICAL DEGRADATIONS OF P-GAN HEMT UNDER HIGH OFF-STATE BIAS STRESS WITH NEGATIVE GATE VOLTAGE | 239 |
| <i>C. Zhang, S. Li, S. Liu, J. Wei, W. Wu, W. Sun</i> | |
| INVESTIGATION OF ELECTRICAL PARAMETERS DEGRADATIONS FOR 600V SOI-LIGHT UNDER REPETITIVE ESD STRESSES | 243 |
| <i>L. Lu, R. Ye, S. Liu, W. Sun</i> | |
| CAPACITOR MODELING METHODOLOGY FOR SYSTEM-LEVEL ESD SIMULATION | 247 |
| <i>L. Xiang, X. Xiaofei, X. Nan, G. Zhengdong</i> | |
| AN EFFICIENT AND NON-DESTRUCTIVE GROUNDING METHOD FOR PASSIVE VOLTAGE CONTRAST FAULT ISOLATION | 251 |
| <i>I. Tee, K. Lee, J. Zhu, Z. Mo</i> | |
| EMMI ABNORMAL HOTSPOT STUDY FOR LATCH UP SIMULATION | 255 |
| <i>C.-S. Huang, X.-C. Guo, Z.-W. Chen, S.-C. Lin, S.-R. Zhang, B.-A. Tsai</i> | |
| GAAS PHEMT SINGLE POLE DOUBLE THROW (SPDT) RF SWITCH FAILURE ANALYSIS | 259 |
| <i>L. Shi, Q. Li, H. Dai, Z. Wang, H. Jing</i> | |
| ELECTRICAL FIELD ACCELERATED GND CORROSION OF COPPER WIRE IN HIGH HUMIDITY CONDITIONS | 262 |
| <i>X. Chen, J. Fang, W. Huang, Y. Wei, C. Chen</i> | |
| UNDERSTANDING LIFETIME PREDICTION METHODOLOGY FOR IN_{0.53}GA_{0.47}AS NFETS UNDER POSITIVE BIAS TEMPERATURE INSTABILITY (PBTI) CONDITION | 266 |
| <i>Z. Ji, X. Zhang, J. Zhang</i> | |
| ENDPOINT DETECTION METHODS IN IMPLEMENTING AI-ASSISTED POLISHING PROCESS | 272 |
| <i>H. Tan, J. Leo, S. Parab, K. Menon, Y. Zhao, Y. Pan, C. Chen, P. Tan</i> | |
| 100V INTEGRATED BOOTSTRAP DIODE WITH DYNAMIC FIELD LIMITING RINGS FOR SOLVING REVERSE RECOVERY FAILURE IN GAN GATE DRIVER ICS | 276 |
| <i>A. Li, S. Li, J. Zhu, L. Zhang, T. Tian, G. Zhu, Y. Zou, H. Zhu, W. Sun</i> | |
| A NOVEL REVERSE CONDUCTING SOI-LIGHT WITH DOUBLE INTEGRATED NMOS FOR ENHANCED REVERSE RECOVERY | 280 |
| <i>A. Li, S. Li, L. Zhang, J. Zhu, T. Tian, Y. Zou, G. Zhu, W. Sun</i> | |

| | |
|--|-----|
| 4-POINT-BENDING CHARACTERIZATION OF INTERFACIAL ADHESION STRENGTH OF CO-ZR-TA AND CO-ZR-TA VARIANT THIN-FILM STACKS | 284 |
| <i>X. Zhu, X. Li, R. Nistala, Z. Ali, L. Peng, L. Selvaraj, C. Cheng, Z. Mo</i> | |
| PLANAR STAINING TECHNIQUE FOR PHOTORESIST RELATED IMPLANTATION ISSUE | 288 |
| <i>L. Li, S. Lee, J. Yang, P. Ang, Z. Mo</i> | |
| CALCULATING ACTIVATION ENERGY (EA) OF SRAM PRODUCT USING THE VMIN VARIATION METHOD | 293 |
| <i>T. Han, K. Chao, H. Chieh</i> | |
| CASE STUDY ON PRECISE BORON QUANTIFICATION OF MIXED MATRIX | 297 |
| <i>K. Ong, Y. Wang, H. Teo, R. Nistala, Z. Mo</i> | |
| DEFECT CHARACTERIZATION BY DIFFERENTIAL PHASE CONTRAST IMAGING TECHNIQUE IN SCANNING TRANSMISSION ELECTRON MICROSCOPE | 301 |
| <i>C.-C. Lin, K. Hsu</i> | |
| AN EFFECTIVE MONITORED AND IMPROVED METHOD TO CONTROL MOISTURE FOR OUTGOING FOSB | 305 |
| <i>Y.-Y. Chen, C.-E. Tseng, H.-W. Fan, C.-C. Pai</i> | |
| APPLICATION OF SIMS FOR THE CHARACTERIZATION OF NITROGEN IN TAN FILM | 310 |
| <i>Y. Wang, H. Teo, K. Ong, N. Phang, P. Ang, X. Li, R. Nistala, Z. Mo</i> | |
| SELECTIVE MECHANICAL BACKSIDE GRINDING OF CSP-BGA AND SOIC-CAV DEVICES IN PREPARATION FOR BACKSIDE FAILURE ANALYSIS | 313 |
| <i>M. Caseria, D. Madrinan</i> | |
| THE APPLICATION OF THERMAL SENSOR TO LOCATE IC DEFECTS IN FAILURE ANALYSIS | 320 |
| <i>K.-C. Huang, Y.-C. Lin</i> | |
| APPLICATION OF NANO-INDENTATION METHOD TO CHARACTERIZE ADHESION STRENGTH OF POLYIMIDE FILM | 325 |
| <i>X. Li, X. Zhu, Y. Liu, X. Li, R. Chockalingam, R. Nistala, Z. Mo</i> | |
| STUDY OF CHARGE NEUTRALIZATION TECHNIQUES TO PREVENT COPPER CORROSION ON POST-FIB WET STAINED SAMPLE | 329 |
| <i>S. Lee, L. Hong, K. Hong, A. Chuan, M. Qiang</i> | |
| RESEARCH ON SRAM EXHIBITING ABNORMAL BEHAVIORS OF ELECTRICAL CHARACTERISTICS AFTER ACCELERATED STRESS IN RELIABILITY | 333 |
| <i>Y. Chen, C. Lo, W.-H. Tseng, Y.-Y. Chen</i> | |
| SIGNAL PROCESSING METHOD FOR SCANNING-AcouSTIC-TOMOGRAPHY DEFECT DETECTION BASED ON CORRELATION BETWEEN ULTRASOUND WAVEFORMS | 337 |
| <i>M. Kobayashi, K. Sakai, K. Sumikawa, O. Kikuchi</i> | |
| REPETITIVE-AVALANCHE-INDUCED ELECTRICAL DEGRADATION AND OPTIMIZATION FOR 1.2KV 4H-SiC MOSFETS | 343 |
| <i>H. Fu, J. Wei, S. Liu, W. Wu, W. Sun</i> | |
| MODELING IC SNAPBACK CHARACTERISTICS USING A VCCS MODEL FOR CIRCUIT-LEVEL ESD SIMULATION | 347 |
| <i>Y. Li, Y. Wang, Y. Wang</i> | |
| RELIABILITY HAZARD CHARACTERIZATION OF WAVER-LEVEL SPATIAL METROLOGY PARAMETERS BASED ON LOF-KNN METHOD | 350 |
| <i>J. Zhang, H. You, R. Jia</i> | |
| REDUCTION OF CURRENT COLLAPSE IN GAN (MIS)-HEMTS USING DUAL MATERIAL GATE | 354 |
| <i>B. Syamal, S. Chiah, X. Zhou</i> | |
| PROVOCATION TESTS, DESIGN OF EXPERIMENTS AND ADVANCED STATISTICAL MODELING TO ESTIMATE PRODUCT SENSITIVITY TO A DEFECT: DELAMINATION FAILURE CASE STUDY FOR AUTOMOTIVE SEMICONDUCTORS | 358 |
| <i>C. Berges, J. Song, C. He, X. Qian, J. Ren, L. Tian, G. Wen, H. Zhang</i> | |
| A SYSTEMATIC FAILURE ANALYSIS APPROACH TO DETERMINE TRUE ELECTRICAL OVERSTRESS FAILURES ON INTEGRATED CIRCUITS | 362 |
| <i>E. De La Cruz</i> | |
| ENHANCING THE SRAM FAILURE ANALYSIS PROCESS | 368 |
| <i>R. Mendaros</i> | |
| LOW-TRIGGER LD莫斯-SCR FOR ESD PROTECTION OF SINGLE PHOTON DETECTOR | 374 |
| <i>Y. Wang, X. Jin</i> | |
| STUDY OF CROSS CONTAMINATION BETWEEN INP SUBSTRATE AND SILICON SUBSTRATE DURING PHOSPHORUS DEPTH PROFILE MEASUREMENT | 378 |
| <i>W. Mengxue, Z. Lei, L. Jiahui, H. Younan, L. Xiaomin</i> | |

| | |
|---|-----|
| HIGH-RESOLUTION 3D X-RAY MICROSCOPY FOR STRUCTURAL INSPECTION AND MEASUREMENT OF SEMICONDUCTOR PACKAGE INTERCONNECTS..... | 382 |
| <i>S. Mohammad-Zulkifli, B. Zee, G. Thomas, A. Gu, Y. Yang, T. Masako, W. Lee</i> | |
| METALLIC TRACE CONTAMINANT DETECTION USING SEM/EDX..... | 386 |
| <i>A. Lee, B. Zee, F. Foo</i> | |
| APPLICATION OF LASER DEPROCESSING TECHNIQUE IN PHYSICAL FAILURE ANALYSIS ON MEMORY BIT-COUNTING | 390 |
| <i>Y. Pan, Y. Zhao, P. Tan, P. Khoo, P. Yeo, S. Ting, H. Tan, C. Chen</i> | |
| INVESTIGATIONS ON THE SHORT-CIRCUIT DEGRADATION AND ITS MECHANISM OF 1.2-KV 19-A SIC POWER MOSFETS | 397 |
| <i>J. Wang, Y. Chen, Z. He, Y. En, X. Xu, Y. Huang, K. Geng</i> | |
| MODELING AND SIMULATION OF DIODE TRIGGERED SILICON CONTROLLED RECTIFIER BEHAVIOR UNDER ESD STRESSES | 401 |
| <i>M. Miao, Y. Li, R. Gauthier</i> | |
| SOFT DEFECT LOCALIZATION (SDL) OF TEMPERATURE DEPENDENT FAILURE USING NI-PXI TEST PLATFORM IN DALS SYSTEM..... | 405 |
| <i>J. Deligente</i> | |
| CHARACTERIZATION OF 1122NM LASER FOR LASER BASED FAULT ISOLATION APPLICATIONS..... | 409 |
| <i>V. Somasundaram, S. Xuan, A. Phoa, W. Lua, C. Meng, V. Ravikumar</i> | |
| DEFECT LOCATION AND PHYSICAL ANALYSIS IN CHIP-ON-CHIP DEVICE | 413 |
| <i>Z. Wang, Z. Wu, J. Sun, C. Duan</i> | |
| IMPROVEMENT OF SENSITIVITY OF ULTRASONIC BEAM INDUCED RESISTANCE CHANGE (SOBIRCH) METHOD WITH ULTRASOUND RESONANCE IN MOLD RESIN | 416 |
| <i>T. Matsui, K. Tatsumi, T. Kawashima, Y. Murakami, N. Hozumi, S. Eura, T. Matsumoto</i> | |
| COMPARISON OF NBTI KINETICS IN RMG SI P-FINFETS FEATURING ATOMIC LAYER DEPOSITION TUNGSTEN (ALD W) FILLING METAL USING B₂H₆ AND SiH₄ PRECURSORS | 421 |
| <i>L. Zhou, G. Wang, X. Yin, B. Tang, Q. Liu, Z. Ji, H. Xu, Z. Kong, H. Jiang, Y. Luo, E. Simoen, H. Yang, H. Yin, A. Du, H. Zhu, C. Zhao, W. Wang, T. Ye</i> | |
| STUDY OF INTERNAL LATCHUP BEHAVIORS IN ADVANCED BULK FINFET TECHNOLOGY | 427 |
| <i>W. Liang, R. Gauthier Jr., S. Mitra, Y. Li, C. Yan</i> | |
| GENERATION AND TRACKING OF OPTICAL SIGNALS INSIDE THE IC TO IMPROVE DEVICE SECURITY AND FAILURE ANALYSIS | 431 |
| <i>E. Amini, N. Herfurth, A. Beyreuther, J.-P. Seifert, C. Boit</i> | |
| INVESTIGATION OF CONDUCTANCE FLUCTUATIONS OF ANALOG RRAM DURING WEIGHT UPDATE PROCESS WITH KINETIC MONTE CARLO SIMULATION | 437 |
| <i>F. Xu, B. Gao, H. Wu, H. Qian</i> | |
| LEAKAGE CURRENT DEGRADATION IN SIC JUNCTION BARRIER SCHOTTKY DIODES UNDER HEAVY ION MICROBEAM | 440 |
| <i>C. Shuang, Y. Qingkui, D. Guanghua, G. Jinlong, W. He, Z. Hongwei, S. Yi</i> | |
| IN-DEPTH ANALYSIS OF 10 NM EXYNOS PROCESSOR USING MICRO CT AND FIB-SEM SYSTEM..... | 444 |
| <i>S. Sharang, J. Dluhos, D. Kalasova, A. Denisyuk, R. Vana, T. Zikmund, J. Kaiser, J. Obona</i> | |
| POLY-SI UNETCH FAILURE DUE TO ETCHING RATE DEPENDENCE OF SI ORIENTATION..... | 448 |
| <i>D. Nam, S. Song, E. Go, B. Chae, A. Kim, B. Kim, H. Kim, J.-S. Yang, S. Han, H. Ryu, S. Chung, B. Lee</i> | |
| BREAKDOWN MECHANISM OF ALGAN/GAN-BASED HFET WITH CARBON-DOPED GAN BUFFER LAYER GROWN ON SI SUBSTRATE | 451 |
| <i>Y. Ni, L. Li, L. He, Y. Liu</i> | |
| CPB FCCSP BGA PACKAGE RELIABILITY ASSESSMENT VIA THE STUDY OF BUMP CROSS SECTION MORPHOLOGY AFTER PRODUCT RELIABILITY STRESS TESTING | 456 |
| <i>H. Hamed, V. Wang</i> | |
| THE IMPACT OF ENDURANCE DEGRADATION IN ANALOG RRAM FOR IN-SITU TRAINING..... | 462 |
| <i>Y. Liu, B. Gao, M. Zhao, H. Wu, H. Qian</i> | |
| THREE-DIMENSIONAL STRUCTURE RECOGNITION OF CIRCUIT PATTERNS ON SEMICONDUCTOR DEVICES USING MULTIPLE SEM IMAGES DETECTED IN DIFFERENT ELECTRON SCATTERING ANGLES | 465 |
| <i>K. Yasui, M. Osaki, A. Miyamoto, H. Namai</i> | |
| IMPACTS OF CHANNEL DOPING ON NBTI RELIABILITY AND VARIABILITY IN NANOSCALE FINFETS | 471 |
| <i>Z. Zhang, R. Wang, Y. Wang, R. Huang</i> | |

| | |
|--|-----|
| SMALL SIGNAL MICROWAVE CHARACTERISTICS AND OPTIMIZATION OF δ-DOPED LAYER POSITIONING IN SUB-MICRON INGAAS HEMT..... | 475 |
| <i>S. Rahman, S. Hatta, N. Soin, Y. Wahab</i> | |
| CORRELATION ANALYSIS AND CHARACTERIZATION OF MICROMORPHOLOGY AND OPTOELECTRONIC PROPERTIES OF SiO_2/SiC IN PRESSURE SENSOR..... | 479 |
| <i>L. Rong, J. He, J. Du, T. Luo, R. Yang, K. Gao, Q. Yu, J. Xu, G. Zhao, Y. Yin</i> | |
| EFFECT OF ACTIVE LAYER THICKNESS ON DEVICE PERFORMANCE AND HOT CARRIER INSTABILITY IN METAL INDUCED CRYSTALLIZED POLYCRYSTALLINE SILICON THIN-FILM TRANSISTORS..... | 483 |
| <i>Z. Jiang, M. Zhang, X. Ma, Y. Yan, G. Li, S. Deng, W. Zhou, R. Chen, M. Wong, H.-S. Kwok</i> | |
| OUTPUT BREAKDOWN CHARACTERISTICS AND THE RELATED DEGRADATION BEHAVIORS IN METAL OXIDE THIN FILM TRANSISTORS | 487 |
| <i>X. Ma, M. Zhang, Z. Jiang, S. Deng, Y. Yan, G. Li, R. Chen, M. Wong, H.-S. Kwok</i> | |
| LIGHT-ILLUMINATION-INDUCED DEGRADATION AND ITS LONG-TERM RECOVERY IN INDIUM-TIN-ZINC OXIDE THIN-FILM TRANSISTORS | 490 |
| <i>M. Zhang, X. Ma, Z. Jiang, S. Deng, G. Li, R. Chen, Y. Yan, M. Wong, H.-S. Kwok</i> | |
| FAILURE ANALYSIS OF MICROWAVE MODULE BY ESD EFFECT | 493 |
| <i>Z. Ding, C. Duan, X. Wang, Z. Wu, Y. Tian, M. Meng</i> | |
| FAILURE ANALYSIS OF THE EFFECT OF HYDROGEN ON GAAS DEVICE | 498 |
| <i>C. Duan, Z. Ding, Z. Wu, X. Wang, C. Li, X. Wang</i> | |
| FAILURE ANALYSIS ON TIAL METALLIZATION PROCESS FOR OHMIC CONTACT ON 4H-SiC PMOSFET | 503 |
| <i>C.-L. Hung, J.-C. Cheng, B.-Y. Tsui</i> | |
| EXPERIMENT CHARACTERIZATION OF FRONT AND BACK INTERFACES IMPACT ON BACK GATE MODULATION IN UTBB-FDSOI MOSFETS | 507 |
| <i>W. Chen, L. Cai, Y. Cao, D. Liao, M. Tian, X. Zhang, X. Liu, G. Du</i> | |
| STUDY OF FRONT-SIDE APPROACH TO RETRIEVE STORED DATA IN NON-VOLATILE MEMORY DEVICES USING SCANNING CAPACITANCE MICROSCOPY | 511 |
| <i>J. Tay, J. Cheah, Q. Liu, C. Gan</i> | |
| ANALYSIS OF TURN-ON UNIFORMITY OF MULTI-FINGER DDSCR DEVICES UNDER ESD STRESS | 515 |
| <i>Y. Wang, D. Jia, X. Chen, X. Jin</i> | |
| FAILURE ANALYSIS AND IMPROVEMENT OF SUPERJUNCTION MOSFET UNDER UIS STRESS CONDITION | 519 |
| <i>M. Ren, Y. Ma, S. Zhong, W. Li, S. Wu, Z. Li, W. Gao, B. Zhang</i> | |
| GATE-VOLTAGE-STRESS-INDUCED INSTABILITY IN $\text{C}_8\text{-BTBT}$ THIN-FILM TRANSISTORS WITH ALUMINIUM OXIDE AS GATE DIELECTRIC | 523 |
| <i>Y. Yan, Z. Huang, X. Ma, Z. Jiang, M. Zhang</i> | |
| COMPARATIVE STUDY OF TOTAL IONIZING DOSE EFFECTS ON THE SILICON-CONTROLLED RECTIFIER DEVICES FOR HV AND LV ESD PROTECTIONS | 527 |
| <i>Z. Chen, W. Lu, M. Wu, W. Peng, Y. Zeng, X. Jin</i> | |
| PRACTICAL DYNAMIC LASER STIMULATION TECHNIQUE AND CODE MODIFICATION: A SOFT DEFECT LOCALIZATION APPROACH FOR MICROCONTROLLER SELF-TEST FAILURES | 531 |
| <i>K. Cala, J. Saludares, W. Basbas</i> | |
| BREAKDOWN VOLTAGE IMPACT ON LIFETIME OF 1200V IGBT MODULES UNDER H3TRB-HVDC TESTING | 539 |
| <i>H. Deng, J. Meng, D.-B. Wang, W. Zhang</i> | |
| ENHANCEMENT OF LOCALIZATION CAPABILITY OF LOCK-IN THERMOGRAPHY FOR POWER SEMICONDUCTOR DEVICES BY SEARCHING HIGH-EMISSIVITY FILMS | 543 |
| <i>N. Chinone, T. Matsumoto, K. Koshikawa</i> | |
| METHODOLOGY TO INVESTIGATE THE ROOT CAUSE OF THRESHOLD VOLTAGE DRIFT OF TRANSISTOR DEVICES USING CAPACITANCE VOLTAGE MEASUREMENTS | 548 |
| <i>A. Keov, M. Negara</i> | |
| A STUDY OF BONDING PAD CORROSION CAUSED BY CONTAMINATION | 552 |
| <i>H. Gan, L. Shi, X. Zhang, H. Dai</i> | |
| EOFM FOR CONTACTLESS PARAMETER EXTRACTION OF LOW K DIELECTRIC MIS STRUCTURES | 555 |
| <i>N. Herfurth, E. Amini, A. Beyreuther, T. Nakamura, S. Keil, C. Boit</i> | |
| EOFM MEASUREMENTS OF LATERAL AND VERTICAL BIPOLAR TRANSISTORS IN SILICON AND SIGE:C TECHNOLOGIES | 560 |
| <i>A. Beyreuther, N. Herfurth, E. Amini, T. Nakamura, G. Fischer, S. Keil, C. Boit</i> | |

| | |
|---|-----|
| INNOVATIVE METHODOLOGY FOR SHORT CIRCUIT FAILURE LOCALIZATION BY OBIRCH ANALYSIS..... | 564 |
| <i>O. Khai, J. Jie</i> | |
| STUDY OF SILICON THICKNESS FOR ELECTRON TRANSPARENCY | 569 |
| <i>H. Tan, B. Liu, M. Chooi, Y. Hua, X. Li</i> | |
| IMPACT OF LOW TEMPERATURE ON THE TSG VT SHIFT DURING ERASE CYCLING OF 3-D NAND FLASH MEMORY..... | 573 |
| <i>D. Li, L. Jin, L. Yan, X. Jia, J. Jia, Y. Song, A. Zhang, F. Xu, W. Hou, Z. Huo, J. Feng</i> | |
| PROBING SRAM SIGNALS FOR YIELD MANAGEMENT | 576 |
| <i>G. Johnson, A. Rummel, M. Kemmler, T. Lundquist, B. Nui</i> | |
| FAILURE ANALYSIS OF SOLDER JOINT CRACKING IN A CBGA ASSEMBLY APPLIED FOR AVIATION EQUIPMENT | 582 |
| <i>H. Xiao, D. Luo, W. Li</i> | |
| SAMPLE PREPARATION IN RECOVER PHYSICAL DEFECTS ON MIM RELATED FAILURE FOR DIFFERENT DEVICES IN WAFER FABRICATION | 586 |
| <i>H. Ng, N. Xu, D. Nagalingam, F. Rivai, A. Teo, P. Tan, C. Chen</i> | |
| AN OVERVIEW OF FAILURE ANALYSIS EXPERT SYSTEM BASED ON BAYESIAN NETWORKS..... | 592 |
| <i>H. Wang, L. Liu, Z. Peng, Y. Wang</i> | |
| RELIABILITY IMPROVEMENT OF RESISTANCE SWITCHING DEVICES BY INSERTION OF A NOVEL 2D MATERIAL MXENE..... | 597 |
| <i>N. He, X. Liu, F. Gao, Y. Wang, M. Zhang, X. Shen, E. Hu, X. Wan, X. Gong, L. He, X. Lian, Y. Tong</i> | |
| ACCURATE MEMORY BITMAPPING BASED ON BUILT-IN SELF-TEST: CHALLENGES AND SOLUTIONS..... | 603 |
| <i>L. Zhao, Y. Ngow, S. Goh, Y. Chan, H. Hu, F. Jeff, C. Tay</i> | |
| FAULT LOCALIZATION USING DYNAMIC OPTICAL-BEAM INDUCED CURRENT VARIATION MAPPING | 611 |
| <i>M. Thor, S. Goh, B. Yeoh, H. Hao, Y. Chan, Z. Lin</i> | |
| A ROBUST DUAL DIRECTIONAL SCR WITHOUT CURRENT SATURATION EFFECT FOR ESD APPLICATIONS | 619 |
| <i>F. Du, X. Dong, C. Yang, Y. Xu, Z. Liu, J. Liu, J. Liou</i> | |
| PUNCH-THROUGH AND DIBL EFFECTS EXPOSING NANO-NODE SOI FINFETS UNDER HEAT STRESS | 623 |
| <i>M.-C. Wang, T.-S. Shen, H.-Y. Bor, C.-N. Wei, W.-S. Liao, W.-H. Lan</i> | |
| CHALLENGE AND SOLUTION FOR CHARACTERIZING NBTI-GENERATED DEFECTS IN NANOSCALE DEVICES..... | 628 |
| <i>J. Zhang, R. Gao, Z. Ji, W. Zhang</i> | |
| RELIABILITY OF 2D FIELD-EFFECT TRANSISTORS: FROM FIRST PROTOTYPES TO SCALABLE DEVICES | 634 |
| <i>Y. Illarionov, T. Grassner</i> | |
| Author Index | |