

2021 IEEE International Symposium on Radio-Frequency Integration Technology (RFIT 2021)

**Hualien, Taiwan
25 – 27 August 2021**



**IEEE Catalog Number: CFP21852-POD
ISBN: 978-1-6654-3392-1**

**Copyright © 2021 by the Institute of Electrical and Electronics Engineers, Inc.
All Rights Reserved**

Copyright and Reprint Permissions: Abstracting is permitted with credit to the source. Libraries are permitted to photocopy beyond the limit of U.S. copyright law for private use of patrons those articles in this volume that carry a code at the bottom of the first page, provided the per-copy fee indicated in the code is paid through Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923.

For other copying, reprint or republication permission, write to IEEE Copyrights Manager, IEEE Service Center, 445 Hoes Lane, Piscataway, NJ 08854. All rights reserved.

****** This is a print representation of what appears in the IEEE Digital Library. Some format issues inherent in the e-media version may also appear in this print version.***

| | |
|-------------------------|-------------------|
| IEEE Catalog Number: | CFP21852-POD |
| ISBN (Print-On-Demand): | 978-1-6654-3392-1 |
| ISBN (Online): | 978-1-6654-3391-4 |

Additional Copies of This Publication Are Available From:

Curran Associates, Inc
57 Morehouse Lane
Red Hook, NY 12571 USA
Phone: (845) 758-0400
Fax: (845) 758-2633
E-mail: curran@proceedings.com
Web: www.proceedings.com

CURRAN ASSOCIATES INC.
proceedings
.com

TABLE OF CONTENTS

| | |
|---|-----------|
| A W-BAND QUADRATURE VOLTAGE-CONTROLLED OSCILLATOR WITH AN INJECTION-LOCKED FREQUENCY DIVIDER IN 40-NM CMOS PROCESS..... | 1 |
| <i>Hao-En Liu; Wei-Cheng Chen; Hong-Yeh Chang</i> | |
| DESIGN OF MECHANICALLY RECONFIGURABLE COUPLERS BASED ON CROSS-SHAPE METALLIC CAVITY FOR 5G MILLIMETER WAVE COMMUNICATION | 4 |
| <i>Yu Fei Pan; Ye Yang; Wing Shing Chan</i> | |
| COMBINED OPTIMIZATION OF FFE AND CTLE EQUALIZATIONS BY ANALYSIS OF PULSE RESPONSE | 7 |
| <i>Yen-Hao Chen; Ding-Bing Lin</i> | |
| CHIP DESIGN OF LOW CONSUMPTION VOLTAGE-CONTROLLED OSCILLATOR WITH EVEN HARMONIC MIXER..... | 10 |
| <i>Wen-Cheng Lai</i> | |
| CMOS THZ PHASED-ARRAY TRANSCEIVERS FOR BEYOND 5G | 13 |
| <i>Kenichi Okada</i> | |
| REVIEW ON NONINVASIVE RADIO-FREQUENCY SENSING FOR CLOSED-LOOP BODY HEALTH MANAGEMENT | 15 |
| <i>J.-C. Chiao; Sen Bing; Khengdauliu Chawang</i> | |
| ADAPTIVE HYBRID BEAMFORMING SCHEMES IN MILLIMETER WAVE MIMO SYSTEMS | 18 |
| <i>Ang-Yun Lu; Yung-Fang Chen</i> | |
| EMBROIDERED COILS – INTEGRATION OF WIRELESS CHARGING RECEIVER COILS IN SMART GARMENTS | 21 |
| <i>Chin-Wei Chang; Patrick Riehl; Jenshan Lin</i> | |
| A WIDEBAND AND HIGH-GAIN 60-GHZ 2×8 MAGNETO-ELECTRIC DIPOLE ANTENNA ARRAY..... | 24 |
| <i>Yu-Chen Yeh; Kuo-Sheng Chin; Xin-Jie Sun</i> | |
| WIDEBAND FILTERING BALUN WITH WIDE STOPBAND AND IMBALANCE COMPENSATION USING HYBRID DGS WITH FLOAT STRIP-LINE..... | 27 |
| <i>Zhiguang Chi; Yunbo Rao; Zhixian Deng; Changxuan Han; Xun Luo</i> | |
| COMPACT BANDPASS FILTER WITH WIDE STOPBAND AND LOW RADIATION USING FULLY-PACKAGED SUBSTRATE INTEGRATED DEFECTED GROUND STRUCTURE | 30 |
| <i>Zhen Peng; Jie Zhou; Yunbo Rao; Zhixian Deng; Xun Luo</i> | |
| A 16-53-GHZ CMOS DOWN-CONVERSION MIXER WITH LINEARIZED ACTIVE BALUN | 33 |
| <i>Mu-Heng Li; Yun-Shan Wang; Huei Wang</i> | |
| EFFICIENT ANALYSIS METHODOLOGIES FOR EMERGING OSCILLATOR CONFIGURATIONS | 36 |
| <i>Almudena Suárez</i> | |
| AN ULTRAWIDEBAND COMMON-MODE FILTER WITH CASCADED MUSHROOM-LIKE STRUCTURES | 39 |
| <i>Yung-Chi Chien; Hsu-Wei Liu; Tzong-Lin Wu</i> | |
| AN EFFICIENT REFERENCE-POINT BASED SURROGATE-ASSISTED MULTI-OBJECTIVE DIFFERENTIAL EVOLUTION FOR ANALOG/RF CIRCUIT SYNTHESIS..... | 42 |
| <i>Sen Yin; Wenyuan Zhang; Wenfei Hu; Zhikai Wang; Ruitao Wang; Jian Zhang; Yan Wang</i> | |
| A FULLY INTEGRATED X-BAND PHASED-ARRAY TRANSCEIVER IN 0.13-μM CMOS TECHNOLOGY | 45 |
| <i>Ruitao Wang; Zhikai Wang; Sen Yin; Jian Zhang; Yan Wang</i> | |
| COMPARATIVE STUDY OF THE CAUSALITY PROPERTY OF VARIOUS CONDUCTOR SURFACE ROUGHNESS MODELS | 48 |
| <i>Chiu-Chih Chou</i> | |
| DESIGN OF A 28-GHZ CMOS RECONFIGURABLE DUAL-FUNCTION SWITCH NETWORK | 51 |
| <i>Kuo-Hung Cheng; Chen-Chung Lo; Sheng-Fuh Chang; Shih-Cheng Lin</i> | |
| A 28/39 GHZ DUAL-BAND POWER AMPLIFIER USING OPTIMAL MATCHING CONTOUR IN GAAS PHEMT..... | 54 |
| <i>Bo-Wei Huang; Zi-Hao Fu; Kun-You Lin</i> | |
| NON-CONTACT VITAL SIGN DETECTION USING GAIN DETECTION TECHNIQUE..... | 57 |
| <i>Kang-Chun Peng; Meng-Che Sung; Fu-Kang Wang; Tzzy-Sheng Horng</i> | |

| | |
|--|------------|
| A MAGNETICALLY COUPLED ALL-PASS PHASE SHIFTER THROUGH HETEROGENEOUS INTEGRATION | 59 |
| <i>Ke-Fan Wu; Jia-Shiang Fu</i> | |
| DESIGN OF QUASI-ELLIPTIC BANDPASS FILTERS BASED ON SHORT-CIRCUITED COUPLED-LINE STUBS | 62 |
| <i>Shih-Fong Chao</i> | |
| A DESIGN OF PERIODIC CIRCUIT ANALOG ABSORBER AT X-BAND AND ITS FABRICATION DISCREPANCY ANALYSIS | 65 |
| <i>Hsi-Tseng Chou; Jake W. Liu; Teng Chang; Yi-Sheng Chang</i> | |
| DUAL-INPUT LNA FOR SWITCHABLE DUAL-CIRCULAR POLARIZATION SATELLITE RECEIVER | 68 |
| <i>Yu-Shiuan Lai; Zi-Hao Fu; Kun-You Lin</i> | |
| DESIGN OF SUB-SAMPLING PHASE-LOCKED LOOP WITH A TIME-BASED LOOP FILTER..... | 71 |
| <i>Tsung-Sheng Chen; Huai-Yuan Hsieh; Liang-Hung Lu</i> | |
| HIGH FREQUENCY AND HIGH SPEED CONNECTOR DESIGN FOR 5G APPLICATIONS | 74 |
| <i>Rung-Bin Hsu; Yu-Cheng Huang; Chia-Che Lee; Ming-Hao Hsieh; Chang-Fa Yang; Chen-Pang Chao; Shih-Chieh Chen; Jaisy Kung; George Wei; Hou-An Su; Hung-Wei Hsu</i> | |
| CMOS DETECTOR BIASED NEGATIVE BODY VOLTAGES FOR SUB-TERAHERTZ IMAGING SYSTEM..... | 77 |
| <i>Jong-Ryul Yang</i> | |
| AN OVERVIEW OF NEURAL NETWORK TECHNIQUES FOR MICROWAVE INVERSE MODELING..... | 78 |
| <i>Jing Jin; Feng Feng; Qi-Jun Zhang</i> | |
| A NUMERICAL METHOD FOR FAST FILTERING ANTENNA ANALYSIS WITH ARBITRARY REFERENCE IMPEDANCES AT MILLIMETER-WAVE FREQUENCIES | 80 |
| <i>Teng Chang; Hsi-Tseng Chou; Chia-Hung Chang</i> | |
| A NEW DESIGN TECHNIQUE FOR POWER AMPLIFIERS OPERATING CLOSE TO UNIT-CURRENT-GAIN CUTOFF FREQUENCY..... | 82 |
| <i>Yi-Fan Tsao; Chien-Ming Tsao; Heng-Tung Hsu</i> | |
| HIGH-OUTPUT CURRENT GALLIUM NITRIDE TRANSCONDUCTANCE AMPLIFIER..... | 85 |
| <i>Arthur L. Torres Costa; Carlos E. Saavedra</i> | |
| WIRELESS POWER TRANSFER COILS WITH REPEATER ARRAY FOR ELECTRIC SCOOTER..... | 86 |
| <i>Ting-Yu Chang; Ming-Lung Kung; Ken-Huang Lin</i> | |
| BROADBAND ON-CHIP TRANSMISSION LINE CHARACTERIZATION USED IN HIGH-SPEED AND HIGH-FREQUENCY COMMUNICATIONS..... | 89 |
| <i>Chien-Chang Huang; Wen-Tsao Fu; Kuan-Chien Cheng</i> | |
| A FLEXIBLE FABRICATION PROCESS FOR THIN SI-SUBSTRATE CHIPS ON MILLIMETER WAVE APPLICATIONS..... | 91 |
| <i>Ming-Jye Wang; Tse-Jun Chen; Yen-Pin Chang; Wei-Chun Lu; Lingzhen Zeng; C. Edward Tong</i> | |
| NONCONTACT VITAL SIGN SENSOR USING SELF-INJECTION-LOCKED (SIL) TECHNOLOGY AND FREQUENCY-TO-POWER CONVERTER (FPC)..... | 94 |
| <i>Fu-Kang Wang; Tzzy-Sheng Horng; Ju-Yin Shih; Ya-Chu Chen; Pin-Hsun Juan; Zhi-Rong Liu</i> | |
| TOWARDS FUTURE DEEPLY INTEGRATED MULTIFUNCTION MILLIMETER-WAVE AND TERAHERTZ SYSTEMS-ON-CHIP | 97 |
| <i>Pascal Burasa; Ke Wu</i> | |
| RECTENNAS FOR WIRELESS ENERGY HARVESTING AND POWER TRANSFER..... | 100 |
| <i>Sumin David Joseph; Shawn S. H. Hsu; Yi Huang</i> | |
| CHARACTERIZATION OF SPIN-ORBIT TORQUE EFFICIENCY IN THE RF REGIME FOR MRAM APPLICATIONS | 103 |
| <i>Tian-Yue Chen; Cheng-Wei Peng; Wei-Bang Liao; Chi-Feng Pai</i> | |
| A LOSS COMPENSATED TUNABLE BANDPASS FILTER BASED ON PARAMETRIC AMPLIFICATION | 109 |
| <i>Siang Chen; Lap K. Yeung; Yuanxun Wang</i> | |
| DUAL-POLARIZATION ANTENNA-IN-PACKAGE OF COLUMN ARRAYS BY LTCC FABRICATION PROCESS FOR HYBRID BROAD AND END-FIRE RADIATIONS AT 28GHZ | 112 |
| <i>Zhi-Da Yan; Hsi-Tseng Chou; Sheng Ju Chou; Joseph D. S. Deng; Chia-Hung Chang</i> | |
| A COMPACT FILTERING POWER DIVIDER WITH QUASI-ELLIPTIC BANDPASS RESPONSE | 114 |
| <i>Hsin-Ya Tseng; Chi-Feng Chen; Dong-Hong Su; Yi-Hua He; Cai-Ni Yu; Bing-Han Wang; Sin-An Chen; Yan-Ting Tu; Wen-Jie Li</i> | |
| RESEARCH ON NOISE DISTRIBUTION OF POWER NETWORK SYSTEM | 117 |
| <i>Wei-Chiao Wang; Sung-Mao Wu; Yuan-Fu Ku; Ming-Shang Lin; Bo-Ting Liu; Hsien-Hung Lin</i> | |

| | |
|--|-----|
| A LOW PHASE NOISE X BAND CLASS E POWER VCO IN 0.25 μM GAN/SIC TECHNOLOGY | 121 |
| <i>Chih-Cheng Chuang; Hwann-Kaeo Chiou</i> | |
| 2.4 GHZ WIDE-TUNING VCO USING SWITCHABLE IMOS-BASED VARACTOR IN 180-NM CMOS | 124 |
| <i>Bo-Han Lee; Yi-Yuang Lin; Tzuen-Hsi Huang</i> | |
| A LOW-POWER DIGITAL VARIABLE-GAIN V-BAND RECEIVER USING CURRENT-REUSED TECHNIQUE WITH EMBEDDED POWER DETECTORS | 127 |
| <i>Yu-Teng Chang; Hsin-Chia Lu</i> | |
| MULTI-TARGET VITAL SIGN DETECTION USING METAMATERIAL LEAKY WAVE ANTENNA-INTEGRATED SUPER-REGENERATIVE OSCILLATOR | 130 |
| <i>Yichao Yuan; Chung-Tse Michael Wu</i> | |
| TRI-BAND DUAL-LINEAR POLARIZED REFLECTARRAY ANTENNA WITH INDEPENDENT BEAM CONTROL | 133 |
| <i>Pei-Ling Chi; Rang Lee</i> | |
| 94 GHZ CRLH SUBSTRATE-INTEGRATED-WAVEGUIDE (SIW) SLOT ANTENNA ARRAY USING SILICON-BASED IPD | 136 |
| <i>Chiao-Yun Hsiao; Chung-Tse Michael Wu; Chien-Nan Kuo</i> | |
| OVERVIEW OF MILLIMETER-WAVE WIRELESS INTERCONNECT | 139 |
| <i>Yanghyo Kim</i> | |
| A 3.5-GHZ 2-W POWER AMPLIFIER IN GAN HEMT TECHNOLOGY | 142 |
| <i>Lung-Yi Chen; Jia-Shiang Fu</i> | |
| EXPERIMENTAL STUDY OF UHF/SHF DUAL-BAND SEMI-LUMPED-ELEMENT POWER DIVIDERS | 145 |
| <i>Ayumu Tsuchiya; Taiji Okuda; Tadashi Kawai; Akira Enokihara</i> | |
| A W-BAND PUSH-PUSH VCO WITH G_M-BOOSTED COLPITTS TOPOLOGY IN 90-NM CMOS TECHNOLOGY | 148 |
| <i>San-Hsien Liu; Chen-Ming Hung; Huey-Ru Chuang; Tzuen-Hsi Huang</i> | |
| A SWITCHABLE DUAL-BAND BANDPASS FILTER WITH FLEXIBLE BAND ALLOCATION | 151 |
| <i>Yi-Hua He; Chi-Feng Chen; Hsin-Ya Tseng; Wen-Jie Li</i> | |
| A 19-GHZ 5-BIT SWITCH-TYPE PHASE SHIFTER DESIGN USING PHASE COMPENSATION TECHNIQUES | 154 |
| <i>You-Jen Liang; Kun-Chan Chiang; Yi-Hsien Lin; Hamed Alsuraistry; Jeng-Han Tsai; Tian-Wei Huang</i> | |
| A 1-WATT 38 GHZ POWER AMPLIFIER USING 0.1-μM GAAS P-HEMT TECHNOLOGY | 157 |
| <i>Jeng-Han Tsai; Geng-Sheng Wei; Yu-Zhe Lin</i> | |
| A K/KA-BAND LOW RMS PHASE ERROR 5-BIT CMOS PHASE SHIFTER | 160 |
| <i>Jeng-Han Tsai; Tai-Ting He; Wu-Hsuan Lin</i> | |
| A 300GHZ CMOS TRANSCEIVER AIMING FOR LONG-RANGE SUB-TERAHERTZ COMMUNICATIONS | 163 |
| <i>Minoru Fujishima</i> | |
| A WIDE TUNING RANGE PHASE LOCKED LOOP FOR 38 GHZ TRANSCEIVER IN 65 NM CMOS | 165 |
| <i>Santosh Kumar Khyalia; Yuen-Sum Ng; Huei Wang; Rajesh Zele</i> | |
| A GAIN ENHANCEMENT STRUCTURE USING 28-NM CMOS PROCESS FOR V-BAND POWER AMPLIFIER APPLICATIONS | 168 |
| <i>Kai-Jie Chuang; Wei-Ting Bai; Yu-Chun Chen; Wen-Jie Lin; Jeng-Han Tsai; Tian-Wei Huang</i> | |
| AN EFFICIENT AND LINEAR 24.4DBM KA-BAND GAAS POWER AMPLIFIER FOR 5G COMMUNICATION | 172 |
| <i>Kai-Jie Chuang; Kin Ping Tang; Yi-Hsien Lin; Tzu-Hung Chen; Chan-Shin Wu; Tian-Wei Huang</i> | |
| A 210.4-DBC/HZ FOMT 67.9% TUNING RANGE LC-VCO IC WITH A SINGLE ANALOG VOLTAGE-CONTROLLED NOVEL VARACTOR IN 40-NM CMOS SOI | 175 |
| <i>Mengchu Fang; Akihiko Kumura; Toshihiko Yoshimasu</i> | |
| 88-96 GHZ VCO WITH INDUCTANCE-COMPENSATED CAPACITIVE SOURCE DEGENERATION IN 90-NM CMOS | 178 |
| <i>Hsin Li; Tzuen-Hsi Huang; Huey-Ru Chuang</i> | |
| A 28-GHZ CLASS-F POWER AMPLIFIER WITH 4096-QAM OFDM UNDER -36.2 DBC EVM IN 28-NM CMOS TECHNOLOGY | 181 |
| <i>Jui-Cheng Hung; Yu-Tung Cheng; Jeng-Han Tsai; Tian-Wei Huang</i> | |
| ANTENNA MUTUAL COUPLING AND GROUND REFLECTION EFFECTS ON THE PERFORMANCE OF A VHF PHASED ARRAY | 184 |
| <i>Liang-Yu Ou Yang; Bingzhang Tsai</i> | |

| | |
|---|-----|
| DEEP INSIGHTS INTO INTERFACE EFFECTS TO ACHIEVE LOW-VOLTAGE OPERATION (<1.2V), LOW PROCESS TEMPERATURE, AND FIRST-PRINCIPLE CALCULATION | 187 |
| <i>Y.-T. Tang; T.-M. Wu; C.-L. Fan; Y.-M. Lai; K.-Y. Hsiang; C.-Y. Liao; S.-H. Chang; T.-Y. Yu; P. Su; M.-T. Chang; B.-H. Huang; C. Hu; S.-J. Chang; M.-F. Chang; M.-H. Lee</i> | |
| DC CHARACTERISTICS AND LOW-FRQUENCY NOISE OF ALGAN/GAN HEMTS WITH DIFFERENT GATE-TO-SOURCE LENGTHS | 189 |
| <i>Shih-Sheng Yang; Yue-Ming Hsin</i> | |
| A 25-31 GHZ LNA IN GAAS 0.15-μM PHEMT | 192 |
| <i>Ling-Yu Lee; Yunshan Wang; Huei Wang</i> | |
| A 5.5GHZ BAND 2-D BEAMFORMING NETWORK USING BROADSIDE COUPLED STRIPLINE STRUCTURE | 195 |
| <i>Jean Temga; Mizuki Motoyoshi; Takashi Shiba; Noriharu Suematsu</i> | |
| A 28-GHZ CMOS TRANSMITTER FOR SILICON PHOTONICS MMWAVE-OVER-FIBER 5G COMMUNICATIONS | 198 |
| <i>Wen-Chieh Huang; Hong-Shen Chen; Yu-Wei Cheng; Chia Chan Tsai; Yung-Shun Huang; Jenny Yi-Chun Liu</i> | |
| A SUB-THZ FREQUENCY DOUBLER WITH QUADRATURE OUTPUTS IN 40-NM CMOS | 201 |
| <i>Ho-Chun Chang; Hong-Shen Chen; Yung-Shun Huang; Jenny Yi-Chun Liu</i> | |
| A CURRENT-REUSE LOW-POWER LNA OPERATED IN MODERATE INVERSION REGION | 204 |
| <i>Kazuya Miyazaki; Takayuki Morishita; Kiyotaka Komoku; Nobuyuki Itoh</i> | |
| EQUIVALENT PROBE MODEL OF NON-CONTACT MEASUREMENT FOR NEAR-FIELD | 207 |
| <i>Tzu-Wen Hung; Hsing-Chuan Peng; Sung-Mao Wu</i> | |
| A 270 GHZ CMOS DOUBLER-BASED UP-CONVERSION MIXER WITH OUTPUT AMPLITUDE IMBALANCE DETECTION | 210 |
| <i>Koki Sekine; Toyoyuki Hagiwara; Kyoya Takano; Shinsuke Hara; Akifumi Kasamatsu; Yohtaro Umeda</i> | |
| MILLIMETER-WAVE CIRCULARLY POLARIZED PATCH ANTENNA WITH ENHANCED AXIAL-RATIO BANDWIDTH | 213 |
| <i>Guan-Ting Chen; Yan-Jhang Gong; Tsenchieh Chiu</i> | |
| DESIGN OF DUAL-FREQUENCY TRANSFORMERS USING THREE EQUAL-LENGTH TRANSMISSION LINES | 215 |
| <i>Chih-Jung Chen</i> | |
| A POLARIZATION SWITCHABLE ANTENNA SWITCH MODULE FOR KA-BAND APPLICATION | 219 |
| <i>Yuan Wang; Yi-Fan Tsao; Chien-Ming Tsao; Hans-Joachim Würfl; Heng-Tung Hsu</i> | |
| CMOS ON-CHIP DUAL L-SHAPED SLOT ANTENNAS | 222 |
| <i>Jerry Shiao; Kun-Ming Chen; Guo-Wei Huang</i> | |
| SUBSTRATE INTEGRATED WAVEGUIDE (SIW) CAVITY RESONATORS: A REVIEW OF TECHNOLOGIES AND APPLICATIONS | 225 |
| <i>Nicolò Delmonte; Lorenzo Silvestri; Luca Perregrini; Maurizio Bozzi</i> | |
| IMPLANT DETECTION USING SELF-INJECTION-LOCKED SENSOR WITH NEAR-FIELD SPLIT-RING RESONATOR | 228 |
| <i>Jyun-Yan Lai; Jheng-Yuan Ruan; Shih-Cheng Lin; Sheng-Fuh Chang</i> | |
| NONCONSTRAINED WRIST PULSE DETECTION SYSTEM BASED ON RF RESONATOR AND PLL | 231 |
| <i>Eun-Gyeol Baek; Jong-Gwan Yook; Byung-Hyun Kim; Gi-Ho Yun</i> | |
| ANALYSIS OF PHASE OFFSET IMPACT ON MILLIMETER-WAVE BROADBAND DOHERTY AMPLIFIER MMIC | 234 |
| <i>Koshi Hamano; Hayato Shimizu; Kenjiro Nishikawa</i> | |
| VIBRATING CLUTTER INTERFERENCE REMOVAL TECHNIQUE IN FMCW RADAR FOR MECHANICAL VIBRATION AND VITAL SIGN DETECTION | 237 |
| <i>Lin Lu; Xujun Ma; Xuwei Fan; Ranbaqiao Hao; Lianming Li; Xiangning Fan</i> | |
| NOVEL UHF RFID TAG ANTENNA DESIGN FOR ELECTRONIC TOLL COLLECTION | 240 |
| <i>Chen-Pang Chao; Yi-Ren Ling; Rung-Bin Hsu; Chang-Fa Yang; Yu-Ming Chen; Dong-Syun Jiang</i> | |
| 5GHZ SIMPLIFIED BEAM FORMING WIRELESS IOT COMMUNICATION USING WI-FI BACKSCATTER | 243 |
| <i>Noriharu Suematsu; Koki Edamatsu; Taiki Machii; Mizuki Motoyoshi; Suguru Kameda; Takashi Shiba</i> | |
| AN INLINE MICROSTRIP-TO-WAVEGUIDE TRANSITION AT 300 GHZ | 245 |
| <i>Kuan-Yung Li; Yu-Hsiang Cheng</i> | |
| A LOW PHASE NOISE 11.8-15.3 GHZ CMOS LC-VCO WITH HIGH-Q INDUCTOR | 247 |
| <i>Kai Sun; Junliang Wang; Xuan Wang; Jiong Gu; Lianming Li; Xiangning Fan</i> | |
| STATIC NOISE MARGIN ANALYSIS FOR CRYO-CMOS SRAM CELL | 250 |
| <i>Vita Pi-Ho Hu; Chang-Ju Liu</i> | |

| | |
|---|-----|
| A 39 GHZ T/R FRONT-END MODULE IN 65NM CMOS | 252 |
| <i>Xuexue Zhang; Kun Qiao; Qin Chen; Yue Liang; Lianming Li; Jun Feng</i> | |
| A BALANCED FILTERING COUPLER WITH FUNCTIONS OF CROSSOVER AND POWER DIVIDER AT DIFFERENT FREQUENCIES | 255 |
| <i>Bo-Ru Wu; Yi-Hsin Pang</i> | |
| HEART RATE EXTRACTION WITH VMD ALGORITHM IN NON-STATIONARY CLUTTER ENVIRONMENT BASED ON FMCW RADAR SYSTEMS | 258 |
| <i>Kuan Ju Wu; Chin-Lung Yang</i> | |
| HIGHLY EFFICIENT HIGH-POWER RECTENNA TECHNIQUES | 261 |
| <i>Kenji Itoh; Naoki Sakai</i> | |
| ANTENNA-ON-DISPLAY AND ANTENNA-IN-PACKAGE TECHNOLOGIES FOR BEYOND 5G CELLULAR HANDSETS: STATE OF THE ART AND PROSPECTS | 265 |
| <i>Junho Park; Wonbin Hong</i> | |
| A 0.5-W 26-31 GHZ POWER AMPLIFIER USING PRE-MATCHING TECHNIQUE IN 0.15-μM PHEMT PROCESS | 266 |
| <i>Sin-Jhe Fe; Shih-Hao Lai; Hong-Yeh Chang</i> | |
| METHODOLOGY OF EMI TREATMENT FOR A LARGE ELECTRICAL VEHICLE | 268 |
| <i>Chi-Fang Huang; Po-Jui Chou; Yi-Hung Hsu; Li-Cheng Hsiao; Chien-Hua Peng</i> | |
| COMPACT DUAL-BAND LNA DESIGN USING A BRIDGED-T COIL-BASED MATCHING NETWORK | 271 |
| <i>Jing-Xuan Chou; Chun-Hao Wei; Yo-Shen Lin</i> | |
| STATUS OF ANALYTICAL OPTIMIZATION OF FET LNAS USING NOISE TRANSFORMATION MATRIX | 274 |
| <i>Chinchun Meng</i> | |
| A G-BAND FREQUENCY DOUBLER IN 40-NM DIGITAL CMOS FOR THZ APPLICATIONS | 277 |
| <i>Chun Wang; Chun-Hsing Li</i> | |
| A LOW-POWER 340-GHZ RECEIVER IN 40-NM CMOS FOR THZ IMAGING APPLICATIONS | 280 |
| <i>Te-Yen Chiu; Chun-Hsing Li</i> | |
| CONTINUOUS-TIME SIGMA-DELTA MODULATOR WITH RF RECEIVER FOR WIRELESS RESPIRATORY DETECTION | 283 |
| <i>Wen-Cheng Lai</i> | |
| HIGH POWER WIDE-BAND GAN AMPLIFIERS: INDUSTRIAL DESIGN AND CHALLENGES | 286 |
| <i>Kamal K. Samanta</i> | |
| Author Index | |