PROCEEDINGS OF SPIE

Metrology, Inspection, and Process Control XXXVII

John C. Robinson Matthew J. Sendelbach Editors

27 February – 2 March 2023 San Jose, California, United States

Sponsored by SPIE

Co-sponsored by Hitachi High-Tech Corporation (Japan) Park Systems Corporation (Korea, Republic of) KLA Corporation (United States)

Published by SPIE

Volume 12496

Part One of Two Parts

Proceedings of SPIE 0277-786X, V. 12496

The papers in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. Additional papers and presentation recordings may be available online in the SPIE Digital Library at SPIEDigitalLibrary.org.

The papers reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from these proceedings: Author(s), "Title of Paper," in *Metrology, Inspection, and Process Control XXXVII*, edited by John C. Robinson, Matthew J. Sendelbach, Proc. of SPIE 12496, Seven-digit Article CID Number (DD/MM/YYYY); (DOI URL).

ISSN: 0277-786X

ISSN: 1996-756X (electronic)

ISBN: 9781510660991

ISBN: 9781510661004 (electronic)

Published by

SPIE

P.O. Box 10, Bellingham, Washington 98227-0010 USA Telephone +1 360 676 3290 (Pacific Time) SPIE.org

Copyright © 2023 Society of Photo-Optical Instrumentation Engineers (SPIE).

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of fees. To obtain permission to use and share articles in this volume, visit Copyright Clearance Center at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher.

Printed in the United States of America by Curran Associates, Inc., under license from SPIE.

Publication of record for individual papers is online in the SPIE Digital Library.



Paper Numbering: A unique citation identifier (CID) number is assigned to each article in the Proceedings of SPIE at the time of publication. Utilization of CIDs allows articles to be fully citable as soon as they are published online, and connects the same identifier to all online and print versions of the publication. SPIE uses a seven-digit CID article numbering system structured as follows:

- The first five digits correspond to the SPIE volume number.
- The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc. The CID Number appears on each page of the manuscript.

Contents

xi Conference Committee

Part One

	KEYNOTE SESSION
12496 03	Overlay challenges in the era of high-NA (Keynote Paper) [12496-1]
	STOCHASTICS
12496 05	Photoresist shrinkage observation by a metrological tilting-AFM [12496-3]
12496 07	Unbiased roughness measurements for 0.55NA EUV material setup [12496-5]
12496 08	SEMI-PointRend: improved semiconductor wafer defect classification and segmentation as rendering [12496-6]
12496 09	Overlay and edge placement error metrology in the era of stochastics [12496-7]
	OPTICAL METROLOGY
12496 OB	Full wafer OCD metrology: increasing sampling rate without the cost of ownership penalty [12496-9]
12496 OC	Sensitivity analysis of optical scatterometry technique for high aspect ratio trench measurement $[12496\text{-}10]$
12496 0D	TSV stress evolution mapping using in-line Raman spectroscopy [12496-11]
12496 OE	Artificial-neural-network-assisted DUV scatterometry for OCD on HAR sub-micron structures [12496-12]
12496 OF	
12470 01	Characterization of asymmetries in 3D NAND memory devices [12496-13]

12496 OH Using active asymmetry control and blind source separation to improve the accuracy of after develop overlay measurements [12496-120] **OVERLAY** 12496 OI Alignment and overlay through opaque metal layers [12496-15] 12496 OJ High spatial frequency on-device overlay characterization using CD-SEM contours [12496-16] 12496 OK SEM ADI on device overlay: the advantages and outcome [12496-17] 12496 OL Massive overlay metrology solution by realizing imaging Mueller matrix spectroscopic **ellipsometry** [12496-18] 12496 OM Machine learning robustness in overlay metrology [12496-19] EPE 12496 ON EPE-aware process optimization for scanner dose and overlay in DRAM use case [12496-20] 12496 OP Multi-metrology: towards parametric yield predictions beyond EPE [12496-22] 12496 0Q Direct yield prediction from SEM images [12496-114] 12496 OR OPO improvements by Moiré effect-based imaging [12496-24] **ELECTRON BEAM METROLOGY I** 12496 OS The rise of contour metrology from niche solution to versatile enabler (Invited Paper) [12496-25] 12496 OT Model validation for scanning electron microscopy [12496-26] 12496 OU Can remote SEM contours be used to match various SEM tools in fabs? [12496-27] 12496 OW Simulating HV-SEM imaging of HAR and buried features [12496-29] **NEW METHODS** 12496 OY A study on defect signal improvement using multi-scan optic patch images and new detection **algorithm** [12496-31]

12496 OZ	EUV grazing-incidence lensless imaging wafer metrology [12496-32]
12496 10	Mueller matrix metrology with multi-angle information using multiple self-interference [12496-33]
12496 11	High-density CD measurement technology with high throughput and high precision on the entire surface of a process wafer, capable of capturing randomly occurring CD defects [12496-34]
	METROLOGY FOR THE EUV ERA
12496 12	Dry resist metrology readiness for high-NA EUVL [12496-35]
12496 13	OPO robustness and measurability improvement via extended wavelengths [12496-68]
12496 14	Multi-modal tabletop EUV reflectometry for characterization of nanostructures (Karel Urbánek Best Student Paper Award) [12496-37]
12496 15	High repeatability and low shrinkage solution using CD-SEM for EUV resist [12496-38]
	3D AND HETEROGENEOUS INTEGRATION
12496 18	Overlay performance in permanent bonded wafer integration schemes [12496-40]
12496 19	Characteristic Mueller matrix responses and correlation analysis for vertical GAA nanowire structure manufacturing using RCWA simulated spectra [12496-84]
12496 1A	Al-guided OCD metrology for single HAR sub-micron via measurement [12496-42]
12496 1B	Detection of bonding voids for 3D integration [12496-43]
	MACHINE LEARNING
12496 1C	Addressing misclassification costs in machine learning through asymmetric loss functions [12496-44]
12496 1D	Self-supervised deep learning neural network for CD-SEM image denoising using reduced dataset [12496-45]
12496 1E	Depth estimation from SEM images using deep learning and angular data diversity [12496-103]
12496 1F	Semiconductor device metrology for detecting defective chip due to high aspect ratio-based structures using hyperspectral imaging and deep learning [12496-47]

12496 1G	Al-guided optical-model-based superresolution for semiconductor CD metrology [12496-48]
12496 1H	Deep learning-based automatic defect classification for semiconductor manufacturing [12496-49]
	EUV AND X-RAY METROLOGY
12496 11	Soft x-ray: novel metrology for 3D profilometry and device pitch overlay (Invited Paper) [12496-50]
12496 1J	Small target compatible dimensional and analytical metrology for semiconductor nanostructures using x-ray fluorescence techniques [12496-51]
12496 1K	Critical dimension measurement: from synchrotron small angle x-ray scattering to industrial optical scatterometry techniques [12496-52]
12496 1L	Reconstruction of the in-depth profile of line gratings with critical dimension grazing incidence small angle x-ray scattering on a laboratory equipment [12496-53]
12496 1M	Pushing the boundaries of EUV scatterometry: reconstruction of complex nanostructures for next-generation transistor technology [12496-54]
	INSPECTION AND KAREL URBÁNEK BEST STUDENT PAPER AWARD PRESENTATION
12496 1N	A novel method for improving yield prediction by matching layout pattern and defect inspection [12496-55]
12496 1N 12496 1O	
	inspection [12496-55] In-situ electrical property quantification of memory devices by modulated electron
12496 10	inspection [12496-55] In-situ electrical property quantification of memory devices by modulated electron microscopy [12496-56] Quantifying CD-SEM contact hole roughness and shape combined with machine learning-
12496 1O 12496 1P	inspection [12496-55] In-situ electrical property quantification of memory devices by modulated electron microscopy [12496-56] Quantifying CD-SEM contact hole roughness and shape combined with machine learning-based pattern fidelity scores for process optimization and monitoring [12496-57] Novel depth quantification technique of buried defect for development of non-destructive
12496 1O 12496 1P 12496 1R	inspection [12496-55] In-situ electrical property quantification of memory devices by modulated electron microscopy [12496-56] Quantifying CD-SEM contact hole roughness and shape combined with machine learning-based pattern fidelity scores for process optimization and monitoring [12496-57] Novel depth quantification technique of buried defect for development of non-destructive
12496 1O 12496 1P 12496 1R	In-situ electrical property quantification of memory devices by modulated electron microscopy [12496-56] Quantifying CD-SEM contact hole roughness and shape combined with machine learning-based pattern fidelity scores for process optimization and monitoring [12496-57] Novel depth quantification technique of buried defect for development of non-destructive optical inspection [12496-59]

12496 1W Advanced high-voltage e-beam system combined with an enhanced D2DB for on-device overlay measurement [12496-166] LATE BREAKING NEWS 12496 1X 300mm in-line metrologies for the characterization of ultra-thin layer of 2D materials [12496-65] 12496 1Y Detection of defective areas and hidden weak patterns in the wafer using massive measurement data [12496-66] 12496 1Z Measurement of W-recess profile in advanced node 3D NAND device with IRCD technology utilizing a specialized design-rule compliant target [12496-85] 12496 20 Enhancement of overlay metrology accuracy by multi-wavelength scatterometry with rotated quadrupole illumination [12496-83] **POSTER SESSION** 12496 22 Tracing optimized condition for electron beam metrology of EUV photoresist pattern using low **landing energy** [12496-136] 12496 24 Scatterometry overlay (SCOL) measurement of small cell target using pupil optimization [12496-67] 12496 25 Machine-learning-based error detection modeling and feature scoring for error cause analysis of CD-SEMs [12496-69] 12496 26 Residuals reduction in imaging-based overlay using color per layer [12496-70] 12496 27 Optimizations of APC multivariate algorithm for linear mix and match overlay control [12496-71] 12496 28 Investigation of device overlay variation and control metrology in 3D-NAND process [12496-72] 12496 29 Novel electron beam technology using InGaN photocathode for high-throughput scanning electron microscope imaging [12496-73] 12496 2A Precise 3D profile measurement of high aspect ratio device patterns by small-angle x-ray **scattering** [12496-74] 12496 2B A study of high-accuracy stand-alone wafer metrology tool for high-productivity of exposure **apparatus** [12496-75] 12496 2C Enabling layer transfer and back-side power delivery network applications by wafer bonding and scanner correction optimizations [12496-76] 12496 2D Optimizing YOLOv7 for semiconductor defect detection [12496-77]

12496 2E	ADI to in-cell overlay stability improvement for DRAM using novel scatterometry and comprehensive process control [12496-78]
12496 2F	Absolute alignment measurement of underlayer and overlayer of diffraction-based overlay mark by image-based alignment metrology system [12496-81]
12496 21	Fourier analysis of spectrum for precision improvement in thickness determined by machine learning [12496-88]
12496 2J	Numerical study of electromagnetic properties of the 3D through silicon via with high aspect ratio [12496-90]
12496 2K	Frame generation methodology in mask tape-out flow and automation application [12496-91]
12496 2L	Local depth monitoring using scanning electron microscopy and its verification using atomic force microscopy [12496-92]
12496 2M	Small imaging overlay metrology targets for advance nodes [12496-93]
12496 2N	Photoelectron beam technology for SEM imaging with pixel-specific control of irradiation beam current [12496-94]
12496 2P	Edge detection using deep learning pipelines for TEM and SEM metrology by proposing generic and specific approaches [12496-96]
12496 2Q	An optical critical dimension (OCD) model analysis on 3nm complementary FET (CFET) gate stacks [12496-97]
12496 2R	Scatterometry and machine learning for in-die overlay solution [12496-98]
12496 2S	On-line real-time detection system for wafer surface defects based on deep learning and generative adversarial network [12496-99]
12496 2T	A generic deep-learning-based defect segmentation model for electron micrographs for automatic defect inspection [12496-100]
12496 2U	The development of a machine learning-based excimer laser performance simulator for engineering maintenance decisions [12496-101]
12496 2V	Mueller matrix spectroscopy and physics-based machine learning for gate-all-around sheet-specific metrology $[12496\text{-}102]$
12496 2W	Determination of deep hole structure for advanced semiconductor devices analyzed by transmission x-ray scattering [12496-104]
12496 2X	Wide-field massive CD metrology based on the imaging Mueller-matrix ellipsometry for semiconductor devices [12496-105]
12496 2Y	A study of diffraction-based overlay (DBO) on a 3nm CFET metal layer [12496-106]
12496 27	A study of 3nm CFFT middle-of-the-line contact layer OCD measurement sensitivity [12496-108

12496 30	Laser assisted SEM for visualizing electrical property using voltage contrast dynamics [12496-109]
12496 31	The role of neutral drag force in pulsed plasma enabled particle contamination control [12496-112]
12496 32	Wafer in process impact simulation caused by lens calibration [12496-113]
12496 33	Die-level nano-topography metrology to characterize the stress-induced in-plane distortion contribution to overlay [12496-115]
12496 34	Ultra-thin uncooled integrable-on-chip detector to measure wide infrared radiation residue in lithography exposure and metrology inspection tools [12496-116]
12496 35	Automatic defect classification (ADC) solution using data-centric artificial intelligence (AI) for outgoing quality inspections in the semiconductor industry [12496-121]
12496 37	Deep learning for the analysis of x-ray scattering data from high aspect ratio structures $[12496-123]$
12496 38	Parallel MEMS AFM for high-throughput semiconductor metrology and inspection [12496-124]
12496 39	Automated (S)TEM metrology characterization of gate-all-around and 3D NAND devices [12496-128]
12496 3A	Parallax method for diffraction-based single-cell overlay and film thickness measurement [12496-131]
12496 3B	Precise optical constant determination in the soft x-ray, EUV, and VUV spectral range [12496-132]
12496 3C	Large field of view metrology: detecting critical edge placement error signatures not seen with small field of view in an HVM environment [12496-133]
12496 3D	Advanced overlay metrology for 3D NAND bonding applications [12496-134]
12496 3E	Tracing optimized condition for electron beam metrology of EUV photoresist pattern using low-landing energy [12496-135]
12496 3F	Comparison between supervised and self-supervised deep learning for SEM image denoising $\left[12496\text{-}137\right]$
12496 3G	New metrology technique for measuring the free shape of a patterned 300mm wafer held vertically [12496-138]
12496 3J	Al-guided reliability diagnosis for 5,7nm automotive process [12496-142]

12496 3K	Wafer yield prediction using AI: potentials and pitfalls [12496-144]
12496 3M	3D measurement using SEM technology [12496-60]
12496 3N	Exploiting spatial characteristic of wafer for effective OCW: area partitioning OCW [12496-192]
12496 30	Effective tool induced shift (eTIS) for determining the total measurement uncertainty (TMU) in overlay metrology [12496-195]
12496 3P	General effective medium model for phonon heat flow in highly confined semiconductor nanosystems [12496-196]