

User's Manual for GeogridBridge 3.0

A Guide to the Load Displacement
Compatibility Method (LDC) for Design of
Column-Supported Embankments

Editors:

**Michael P. McGuire
Elise G. Hummel**

**Eric M. Hunstein
Joel A. Sloan**

ISBN: 979-8-3313-0341-9

Printed from e-media with permission by:

Curran Associates, Inc.
57 Morehouse Lane
Red Hook, NY 12571

Some format issues inherent in the e-media version may also appear in this print version.

Copyright© (2024) by American Society of Civil Engineers
All rights reserved.

Printed with permission by Curran Associates, Inc. (2024)

For permission requests, please contact American Society of Civil Engineers
at the address below.

American Society of Civil Engineers
1801 Alexander Bell Drive
Reston, VA 20191
USA

Phone: (800) 548-2723
Fax: (703) 295-6333

www.asce.org

Additional copies of this publication are available from:

Curran Associates, Inc.
57 Morehouse Lane
Red Hook, NY 12571 USA
Phone: 845-758-0400
Fax: 845-758-2633
Email: curran@proceedings.com
Web: www.proceedings.com

Contents

Contributors.....	ix
Acknowledgments.....	xi
Preface.....	xiii
Notation.....	xv
Chapter 1 Introduction.....	1
References	3
Chapter 2 Spreadsheet.....	5
2.1 General.....	5
2.2 Units	7
References	8
Chapter 3 Inputs.....	9
3.1 Defining Profile and Stratigraphy.....	9
3.2 Material Properties for Soil Arching.....	11
3.2.1 Embankment Soil Properties	11
3.2.2 Mobilization of Arching.....	11
3.3 Material Properties for Negative Skin Friction.....	12
3.4 Material Properties for Compression	13
3.4.1 Sands.....	13
3.4.2 Clays	13
3.4.3 Columns.....	14
3.5 Stress Adjust	14
3.6 Loading Conditions	16
3.7 Column Geometry	17
3.8 Geosynthetic Reinforcement	17
References	18
Chapter 4 Monte Carlo Simulation	21
4.1 Number of Trials.....	21
4.2 Acceptable Output Values	22
4.3 Distribution Type.....	22
4.4 Soil Parameter Variability	23
References	25

Chapter 5 Outputs.....	27
References	28
Chapter 6 Simple Worked Example	29
6.1 Problem Statement.....	29
6.2 Define Postconstruction Profile	30
6.3 Define Material Properties for Each Layer	30
6.4 Determine Surface Loading Conditions.....	32
6.5 Input Column Geometry.....	32
6.5.1 Array Geometry.....	32
6.5.2 Cap Shape and Geometry	32
6.5.3 Column Shape and Geometry	33
6.6 Specify Geosynthetic Reinforcement Stiffness.....	33
6.7 Select the Desired Method for Modeling the Mobilization of Arching.....	34
6.8 Run the Spreadsheet.....	35
6.9 Analyze the Results.....	35
6.10 Run a Batch Analysis.....	36
6.10.1 Select the Number of Trials.....	36
6.10.2 Define Serviceability Limits	36
6.10.3 Select Parameters to Vary	37
6.10.4 Run the Batch Analysis	39
6.10.5 Analyze the Results.....	39
References	40
Chapter 7 Complex Worked Example.....	41
7.1 Problem Statement.....	41
7.2 Develop a Postconstruction Profile	42
7.3 Define Material Properties for Each Layer	43
7.3.1 General Embankment.....	43
7.3.2 Load Transfer Platform	44
7.3.3 Sand 1	44
7.3.4 Clay 1	44
7.3.5 Sand 2	45
7.3.6 Clay 2.....	46
7.4 Determine Surface Loading Conditions.....	47
7.5 Input Column Geometry.....	47
7.6 Specify Geosynthetic Reinforcement Stiffness.....	48
7.7 Select the Desired Method for Modeling the Mobilization of Arching.....	48
7.8 Run the Spreadsheet.....	49
7.9 Analyze the Results.....	49
7.10 Run a Batch Analysis.....	50
7.10.1 Select the Number of Trials.....	50
7.10.2 Define Serviceability Limits	50

7.10.3 Select Parameters to Vary	51
7.10.4 Run the Batch Analysis	54
7.10.5 Analyze the Results.....	54
References	55
Index.....	57